



**KRYTAC®**

# ALPHA CRB



## SPECIFICATIONS

All specifications subject to change.

Caliber:	6 mm
Overall Length:	711 mm (28") - 795 mm (31.3")
Overall Height:	180 mm (7")
Weight:	2.38 kg (5.24 lbs)
Outer Barrel Length:	266.7 mm (10.5")
Inner Barrel Length:	280 mm
Inner Barrel Diameter:	6.05 mm

### EXTERNAL FEATURES

- ALPHA 9" metal hand guard
- KRYTAC metal alloy receivers
- KRYTAC battery stock
- Ambidextrous fire selector
- MIL-STD 1913 Picatinny top rail
- Locking bolt and bolt release
- 6-position numbered buffer tube
- Ambidextrous sling loops
- Adjustable iron sights

### INTERNAL FEATURES

- 8mm ball bearing mechbox
- Integrated FET system
- Easy maintenance spring guide
- Padded cylinder head
- Relief-cut cylinder window
- Anti-corrosion mechbox coating
- Adjustable rotary hop-up
- Temperature and wear resistant hop-up bucking
- KRYTAC 20K motor



**RATE OF FIRE**  
18+ RPS



**VELOCITY** (with 0.20g BB)  
Min: 290 FPS / 88 MPS  
Max: 310 FPS / 95 MPS

\*Performance details are based on U.S. specifications and can be modified to meet the laws and regulations of your local region.