

ALPHA SDP



SPECIFICATIONS

All specifications subject to change.

Caliber:	6 mm
Overall Length:	480 mm (19") - 565 mm (22.25")
Overall Height:	180 mm (7")
Weight:	2.4 kg (5.3 lbs)
Outer Barrel Length:	140 mm (5.5")
Inner Barrel Length:	135 mm
Inner Barrel Diameter:	6.05 mm

EXTERNAL FEATURES

- KRYTAC metal alloy receivers
- KRYTAC aluminum hand guard
- Two-position compact carbine stock
- MIL-STD 1913 Picatinny top rail
- Ambidextrous fire selector
- Locking bolt and bolt release
- Sling attachment loop

INTERNAL FEATURES

- 8mm ball bearing mechbox
- Integrated FET system
- Easy maintenance spring guide
- Padded cylinder head
- Relief-cut cylinder window
- Anti-corrosion mechbox coating
- Adjustable rotary hop-up
- Temperature and wear resistant hop-up bucking
- KRYTAC 20K motor



RATE OF FIRE
18+ RPS



VELOCITY (with 0.20g BB)
Min: 275 FPS / 84 MPS
Max: 290 FPS / 88 MPS

Datasheet is based on U.S. specifications, information may vary by region.