



KRYTAC®

TRIDENT MK II : CRB Flat Dark Earth



SPECIFICATIONS

All specifications subject to change.

Caliber:	6 mm
Overall Length:	675 mm (26.5") - 787 mm (31")
Overall Height:	223 mm (8.75")
Weight:	2.5 kg (5.5 lbs)
Outer Barrel Length:	266.7 mm (10.5")
Inner Barrel Length:	280 mm
Inner Barrel Diameter:	6.05 mm

EXTERNAL FEATURES

- KRYTAC MK II metal alloy receivers
- Licensed DEFIANCE® TR110 keymod hand guard
- Licensed DEFIANCE® pistol grip
- KRYTAC battery stock
- Ambidextrous fire selector
- Licensed CMC trigger
- MIL-STD 1913 Picatinny top rail
- Ambidextrous sling loops
- Adjustable iron sights

INTERNAL FEATURES

- 8mm ball bearing mechbox
- Integrated FET system
- Easy maintenance spring guide
- Padded cylinder head
- Relief-cut cylinder window
- Anti-corrosion mechbox coating
- Adjustable rotary hop-up
- Temperature and wear resistant hop-up bucking
- KRYTAC 30K high torque motor



RATE OF FIRE
20+ RPS



VELOCITY (with 0.20g BB)
Min: 365 FPS / 111 MPS
Max: 385 FPS / 117 MPS

*Performance details are based on U.S. specifications and can be modified to meet the laws and regulations of your local region.