



**KRYTAC®**

# TRIDENT MK II : SPR



## SPECIFICATIONS

All specifications subject to change.

Caliber:	6 mm
Overall Length:	863 mm (34") - 945 mm (37.25")
Overall Height:	223 mm (8.75")
Weight:	2.7 kg (5.9 lbs)
Outer Barrel Length:	406 mm (16")
Inner Barrel Length:	416 mm
Inner Barrel Diameter:	6.05 mm

### EXTERNAL FEATURES

- KRYTAC MK II metal alloy receivers
- Licensed DEFIANCE® TR113 keymod hand guard
- Licensed DEFIANCE® pistol grip
- KRYTAC battery stock
- Ambidextrous fire selector
- Licensed CMC trigger
- MIL-STD 1913 Picatinny top rail
- Ambidextrous sling loops
- Adjustable iron sights

### INTERNAL FEATURES

- 8mm ball bearing mechbox
- Integrated FET system
- Easy maintenance spring guide
- Padded cylinder head
- Relief-cut cylinder window
- Anti-corrosion mechbox coating
- Adjustable rotary hop-up
- Temperature and wear resistant hop-up bucking
- KRYTAC 30K high torque motor



**RATE OF FIRE**  
20+ RPS



**VELOCITY** (with 0.20g BB)  
Min: 400 FPS / 122 MPS  
Max: 420 FPS / 128 MPS

\*Performance details are based on U.S. specifications and can be modified to meet the laws and regulations of your local region.